

OPHELIA III

Ophelia III is a high-powered linear track light. Using 9 HIGH POWER LUXEON K2 with TFFC LEDS, this unit offers excellent light output in any installation. The unit is available in a variety of single LED colours and can be mounted to almost any surface. Each individual flood fitting is multi directional using the bracket system on the unit.

LIGHTING PERFORMANCE
LIGHT SOURCE: LUXEON K2 with TFFC
LED QTY: 3 PER FLOOD (9 IN TOTAL)
OUTPUT: 1053 lm TYPICAL
NB- BASED ON 9 COOL WHITE (6500K)
LIFE: 50,000 HOURS +
ELECTRICAL DATA
DRIVE CURRENT: 350mA or 700mA
INPUT VOLTAGE: 3.37V
DRIVER TYPE: CONSTANT CURRENT
CONNECTION TYPE: FLYING LEAD
LUMINAIRE DATA
TEMP RANGE: -10°C to 40°C
MOUNTING TYPE: SCREW FIT
COLOURS: R, G, B, WW, CW, NW, A
FINISHES: SILVER ANODISED
IP RATING: IP67
OPTICS: NARROW, MEDIUM AND WIDE
DIMENSIONS: SEE TECHNICAL DRAWING
THIS PRODUCT COMES COMPLETE WITH CONSTANT CURRENT DRIVER



TECHNICAL DRAWING

