

Sirius II

Wall mounted 6LED Up & Down lighter



FEATURES

- Vandal-resistant PC fronts
- Powered by Seoul Semi P4
- Weatherproof to IP67
- 700mA max drive current
- Tough & durable machined aluminium housing.

DESCRIPTION

SIRIUS II can be mounted as an up or down light.

It is a high-powered wall mounting miniature flood light, using the latest LED and optic technology incorporating 3 high power Seoul Semiconductor P4 LED's the unit offers excellent light output for various applications including wall lighting, mood and effect lighting, architectural lighting or bar and club venues. The unit is available in a variety of single LED colours and can be mounted to almost any surface. The unit is IP67 rated for indoor or outdoor use.

RECOMMENDED DRIVERS

Model
D18CC350-1-7IP67
D18CC700-3-6IP67

LIGHTING PERFORMANCE			
Light Source	LED Qty	Lumen Output	Expected Lifetime
Seoul Semi P4	6	960 @ 700mA	50,000hrs +

N.B. Lumen values quoted on Cool white (6500k)

INPUT DATA			
Drive Current	Input Voltage	Power Supply Type	Input Connection
350-700mA	N/A	Constant Current Drive	500mm Flying Lead

OPERATING DETAILS	
Input power	Ambient Temp Range
15W @ 700mA	-10 to +40 Degrees C

PHYSICAL DETAILS		
Mounting Type	Finish	Ingress Protection
Wall mounted	Matt Silver Anodising	IP67

OPTIONS	
Single LED Colours	Optic
Red, Green, Blue, Amber, Cool White, Neutral White, Warm White	Narrow, Medium, Wide

